FLEXDRAIN®



TEMPERATURE MAINTENANCE SYSTEMS

www.flexelec.com

CSC2K - Silicon elastomer insulated drain-line heaters with integrated thermostat



Characteristics

- · Integrated thermostat.
- · Heating section fully sealed.
- Double insulation.
- · Extremely flexible.
- Voltage 230 V as standard.
- Power cable: length 1 m as standard.

Applications

CSC2K heaters are designed to be placed at the bottom of collector trays inside refrigeration equipment in cold rooms, to prevent freezing and to allow condensate water to flow freely.

The integrated thermostat makes them fully autonomous. It must not be immersed.

Note: The most commonly used power rating is 50 W/m. However, for plastic trays, we strongly recommend using the 40W/m range.





Wire terminated

in the cold tail

Black mark

Silicon elastomer

Silicon elastomer insulation Heating wire Fibre glass core Conductor cable

Standard models

<u></u>			
		CSC2K	
	Length (m)	40 W/m	50 W/m
	1	40 W	50 W
	1.3	52 W	65 W
	1.5	60 W	75 W
	2	80 W	100 W
	3	120 W	150 W
	4	160 W	200 W
	5	200 W	250 W
	6	240 W	300 W

Termination 18 x 16 mm with thermostat

Caution

These cables must never be cut to shorten the cold tail. The round part of the thermostat (sensor) must be placed in the best position to collect information so that the cable can operate as required.

Drain-line cables are series resistors. Consult the pages of the catalogue devoted to the corresponding general operating principles, general instructions for use and accessories

Heating wire Insulation

> Section Power

Voltage

Permissible surface temperature

Tolerances

End insulation Thermostat

CSC2K

Nickel-Chrome or Nickel-Copper

Silicon elastomer

5 x 7 mm

40 or 50 W/m

230 V as standard

from - 40° C to + 110° C

Power: ± 10 % Section: + 0.2 / - 0.1 mm Length: ± 1 %

Heat-shrink sheath with adhesive Pre-set to + 5°C/+ 15°C as standard

FLEXELEC S.A.S

10, rue des frères Lumière Z.A. du Bois Rond 69720 ST BONNET DE MURE - FRANCE Tel: +33 (0)4.72.48.30.90 Fax: +33 (0)4.78.40.82.81

FLEXELEC Dept

OMERIN ASIA Pte Ltd 51 Goldhill Plaza #08-12/01 SINGAPORE 308900 Tel: + 65.6255.4778 Fax: + 65.6255.4779 F-mail: sales@omerin.com.sq.

FLEXELEC (UK) Ltd

FLEXELEC (UK) Lta Unit II Kings Park Industrial Estate Primrose Hill - KINGS LANGLEY Hertfordshire - WD4 8ST - UK Tel: + 44 (0) 1923.274477 Fax: + 44 (0) 1923.270264

FLEXELEC Dept

OMERIN GmbH Buchwiese 16 D-65510 IDSTEIN - GERMANY Tel: + 49 (0) 6126.94.31-0 Fax: + 49 (0) 6126.83.99